




- Forma modellabile
 - Remarkable form
 - Infinite possibilità di design
 - Endless design possibilities
 - Ottica unica
 - Unique optics
 - Alternativa base su picchetto regolabile
- Based on adjustable stake

Luce LED Ramet | Ramet LED light



Electrical data	
Input voltage:	AC 230V /50Hz
Power consumption:	5 W
Efficiency:	85%
PFC:	>90
Life span:	>50.000
Light control:	/
Optical technical data	
LED QTY:	3
Luminous flux(4000K,85°C):	340 lm
Color temperature:	4000K, custom*
CRI:	>80
Luminous efficacy:	68 lm/W
Light angle:	270°
Mechanical data	
Operating temperature:	-25°C ~ +40°C
Dimensions	/
Recessed opening:	/
Weight:	3 kg (small) 7,6 kg (big)
Color and materials	
Color:	chrome, black
Material:	aluminium
Certificates & standards	
IP protection:	IP 65
Protection class insulation	class II (safety insulation)

Specifiche tecniche | Technical data

Vantaggi del prodotto | Product benefits

Luce scenografica per interno ed esterno
 Decorative lighting for inside and outside use.

Ottica singola di puro vetro
 Unique optics from pure glass
Infinite possibilità di design grazie ai tubi flessibili
 Endless design possibilities with flexible tubes.

Migliore gestione termica ottimizzata con dissipatore in alluminio
 Great thermal management with optimized aluminium heat sink.

Sviluppato e realizzato in Europa con 3 anni di garanzia
 Developed and made in Europe with 3 year warranty.

"Come rami leggeri...
 i cui boccioli diventano
 lucciole nella notte..."

"Like light branches ...
 whose buds become
 fireflies in the night ..."

